

Marked-Up Version of Substitute Specification

~~METHOD FOR TRANSMITTING MESSAGES IN AN MMS-BASED COMMUNICATION SYSTEM~~

Description

~~Method for transmitting messages~~

SPECIFICATION

TITLE OF THE INVENTION

METHOD FOR TRANSMITTING MESSAGES IN AN MMS-BASED COMMUNICATION SYSTEM

FIELD OF TECHNOLOGY

The present ~~invention~~-disclosure relates to a method for transmitting messages and in particular a method for transmitting messages with useful data objects according to the Multimedia Messaging Service (MMS) from one telecommunication device to a further telecommunication device.

BACKGROUND

3GPP (3rd Generation Partnership Project) and the OMA (Open Mobile Alliance) specify the so-called Multimedia Messaging Service (MMS) for transmitting data, in particular multimedia data objects, from a first to a second mobile telephone or mobile radio device in a mobile radio communication network. Should a first user ~~thereby~~-wish to send a second user a useful data object, for example in the form of an image or a music file, ~~said-the~~ user uses ~~their-a~~ (first) mobile telephone to send a multimedia message (MM) with the useful data object to a switching component in the communication network, which comprises at least ~~a-so-called~~one MMS relay server. A multimedia message (MM) can also contain a plurality of useful data objects. As a special ~~service-service~~, the MMS provider can individually adapt the at least one useful data object to be delivered ~~for-example~~ to the characteristics or capabilities of the second mobile telephone before sending a further message (hereafter referred to as ~~the-recipient~~ "recipient notification message") to the second mobile telephone of the second user with the information that a multimedia message (MM) with at least one useful data object is available for downloading. One disadvantage of such a method is that the recipient

(in this instance the second user) of a recipient notification message or a multimedia message (MM) with at least one useful data object is unable to identify whether and how the transmission message (hereafter referred to as the multimedia message (MM)) or the useful data object contained therein has been modified and whether the possibly modified useful data object can still be used.

SUMMARY

~~It is therefore the object of the present invention to create a possibility~~Accordingly, the present disclosure describes exemplary embodiments for transmitting useful data objects to a recipient that allows greater control of the useful data objects to be received.

~~This object is achieved by the subject matter of the independent claims. Advantageous embodiments are set out in the subclaims.~~

A One exemplary method for transmitting messages, ~~in particular~~ in a communication network, ~~thereby~~ comprises the following ~~steps~~steps: First a transmission message with one or more useful data objects or multimedia message elements is transmitted to a switching component for forwarding to a first telecommunication device. ~~Such~~This transmission can ~~thereby~~ take place from a sending telecommunication device such as a mobile radio device or a mobile telephone. A plurality of variants of the one or more useful data objects is created in the switching component as a function of a set of parameters. ~~Variant~~“Variant” here refers to both the original form of the one or more useful data objects and the adapted or modified versions. The first telecommunication device, which again can be a mobile radio device or a mobile telephone, is then informed of the availability of a plurality of variants of the one or more useful data objects for transmission to the first telecommunication device. If a recipient, i.e. a user of the first telecommunication device, selects one or more variants of the useful data objects, a delivery request message relating to a specific variant of the one or more useful data objects is advantageously sent from the first telecommunication device to the switching component. A delivery message with the requested variant of the one or more useful data objects is then transmitted from the switching component to the first telecommunication device. Informing the recipient of the different adapted

variants of the useful data objects contained in the transmission message available on the switching component allows the recipient specifically to select and download particular variants of the required useful data objects or the entire transmission message, giving them greater control of the messages or useful data objects they are to receive. Information about the useful data objects available on the switching component also allows the recipient to decide not to initiate a download process at all, if the useful data objects are not of ~~use-use,~~ or if the download process would be very expensive. ~~On the one hand it~~ It is thereby possible to prevent useful data objects being downloaded (from the switching component) to the first telecommunication device if they cannot be used by the telecommunication device and ~~on the other hand it is~~ also possible to specifically ~~to~~ download useful data objects, the size of which has been minimized, thereby minimizing download costs and also allowing a larger number of useful data objects to be stored on the first telecommunication device. The described method also allows the recipient to decide, on the basis of the information about the useful data objects available on the switching component, specifically to download useful data objects which, although they cannot be played back by the second telecommunication device, may be able to be played back by a further device connected to the second telecommunication device either by cable, infrared interface (e.g. IrDA) or radio (e.g. Bluetooth). One possible application is the downloading of a high-quality image file by the second telecommunication device, said file then being printed out using an external printer.

According to an advantageous ~~embodiment-embodiment,~~ the recipient or first telecommunication device is informed as ~~follows-follows:~~ Recipient notification messages assigned to a specific variant of the one or more useful data objects are generated by the switching component and these respective recipient notification messages are transmitted from the switching component to the first telecommunication device.

According to a further advantageous ~~embodiment-embodiment,~~ the set of parameters, as a function of which the plurality of variants of the one or more useful data objects is created, includes parameters with information about the individual characteristics of the telecommunication device. The individual

characteristics of the telecommunication device can also include characteristics of applications provided on the telecommunication device. The set of parameters can also include parameters with information about the individual preferences of the recipient or the set of parameters can include parameters with descriptive information including the significance of useful data objects contained in the transmission message and/or the relationship of the contained useful data objects to each other (so-called metadata, for example according to the MPEG-7 standard).

According to ~~an advantageous embodiment~~the embodiment, the messages ~~can be~~are transmitted in the context of the multimedia messaging service (MMS) between the first telecommunication device, the switching component and the second telecommunication device. This allows the transmission of useful data objects that can also include multimedia content such as digital images, video clips or large audio or music files.

~~According to an advantageous embodiment~~Furthermore, the first telecommunication device and any further telecommunication devices as well as the switching component are preferably part of a telecommunication network. The telecommunication device or further telecommunication devices can thereby be part of a first telecommunication network (in the case of a plurality of telecommunication devices however these do not have to be part of the same telecommunication network). The switching component, which is configured in particular as a server of a data transmission service, such as an MMS relay server, can correspondingly be provided in a second telecommunication network, which is connected to the telecommunication network(s), which is/are assigned to the telecommunication device or further telecommunication devices. This second telecommunication network can be configured in particular as a telecommunication network based on internet protocols, such as the hypertext transfer protocol.

In order to be able to use the method for transmitting useful data objects as flexibly as possible, the messages to and from the first and/or second telecommunication device can be sent via an air interface, whereby the telecommunication device (or even the further telecommunication devices) can preferably be configured as a mobile telecommunication device and can thereby

comprise a radio module or mobile radio module in particular. The transmission of messages to and from a respective telecommunication device can then take place on the basis of the WAP wireless session protocol (WSP) or the hypertext transfer protocol (http). The telecommunication device can thereby be configured ~~for example~~ as a mobile radio device or mobile telephone, a cordless telephone, a smartphone (combination of a small portable computer and a mobile telephone), a PDA (personal digital assistant) or an organizer. The telecommunication device can also include other devices with mobile access such as a personal computer (PC) or a laptop, which can be accessed via a mobile radio network by means of a connected mobile radio device (mobile telephone). The mobile radio device can then ~~for example~~ be connected via a cable to the personal computer or laptop or can even contact these wirelessly via an infrared interface or a local Bluetooth network. A telecommunication device, such as the mobile radio device, including the telecommunication network assigned to it, can thereby operate in the form of a mobile radio network according to the GSM (Global System for Communication) standard or the UMTS (Universal Mobile Telecommunications System) standard, etc. Such mobile radio networks or telecommunication devices according to the GSM or UMTS standard can represent a platform for WAP (Wireless Application Protocol) protocols or the WAP protocol stack, by means of which data (notifications or useful data objects) can be transmitted in the respective mobile radio network.

The first and second telecommunication networks are advantageously preferably connected together by means of a connecting component. If the WAP protocol stack is used, as mentioned above, it is possible to create a connection to this, by using a WAP gateway as the interface or connecting component between a mobile radio network and another network, for example an internet protocol-based network. This makes it possible for the switching components to be located in an internet protocol-based network, such as the internet, whereby the data (messages, useful data objects) can be transmitted via a WAP gateway and ultimately via an air interface of a mobile radio network between the base station(s) of the mobile radio network and to the respective user telecommunication devices. It should be

mentioned here that in the context of the MMS data transmission ~~service-service~~, in particular—messages can be sent from the MMS relay server as the switching component automatically, i.e. without prompting a telecommunication device, to a telecommunication device by means of WAP push. The MMS relay server hereby serves as a so-called push initiator, activating the WAP gateway or a sub-component thereof, namely the push proxy gateway, to send a message by WAP push to the telecommunication device. For example according to the MMS transmission service the recipient notification message is transmitted by WAP push to the telecommunication device.

It should be pointed out that the useful data objects can generally include audio information, video information, executable programs, software modules or a combination of such information.

According to a further ~~aspect of the invention~~embodiment a telecommunication arrangement is created comprising a switching component and at least a first telecommunication device, the telecommunication arrangement being configured to implement a method as set out above.

~~Preferred embodiments of the present invention are described in more detail below with reference to the accompanying drawing, in which:~~

BRIEF DESCRIPTION OF THE DRAWINGS

The various objects, advantages and novel features of the present disclosure will be more readily apprehended from the following Detailed Description when read in conjunction with the enclosed drawings, in which:

Figure 1 shows a schematic illustration of a communication network or telecommunication network for implementing ~~the~~an MMS system, in which two service providers are provided for an MMS environment;

Figure 2 shows a schematic illustration of ~~possible~~exemplary interfaces of an MMS relay server;

Figure 3 shows an exemplary ~~process~~(transaction flow diagram) for transmitting a multimedia message from a mobile radio device to a second mobile radio device;

Figure 4 shows a detailed illustration of the interface MM1 shown in figure 2, in which a WAP gateway ensures the adaptation of the MMS useful data to the two different session layer protocols (WSP and HTTP);

Figure 5 ~~shows~~—illustrates a section of a user interface of a telecommunication device for displaying the options or information provided in recipient notification messages according to a first embodiment; and

Figure 6 shows a section of a user interface of a telecommunication device for displaying the options or information provided in recipient notification messages according to a second embodiment.

DETAILED DESCRIPTION

Before going on to describe a method for transmitting messages, in particular by means of the MMS (Multimedia Messaging Service), from one telecommunication device to a second telecommunication device according to a preferred embodiment of the invention, it is ~~first~~ necessary once again to describe the basic components or network structures for implementing an MMS service.

For next generation mobile systems (2.5G and 3G), such as systems operating according to the UMTS (Universal Mobile Telecommunications System) standard, a multimedia-enabled variant of a mobile message service is at present standardized, namely the MMS service or MMS. MMS messages with multimedia content are referred to below, for a clearer distinction from SMS (Short Message Service) text messages, simply as MMs (Multimedia Messages). Unlike SMS there is no restriction to pure text content. With MMS it is possible to format texts to individual tastes and to embed audio and video content in a message. An MM can therefore contain a number of MM elements or useful data objects of different file types (e.g. audio or stills) or file formats (e.g. GIF or JPEG for stills). A temporally defined sequence of small presentations is also possible.

Figure 1 shows a possible telecommunication arrangement or network architecture KN for implementing the MMS, in particular according to a 3GPP (3rd Generation Partnership Project) specification. On the left of the figure is a first telecommunication device configured as a first mobile radio device MFG1, which is connected via an interface, more precisely an air interface, as will be described in

more detail with reference to figure 2, to a communication network (to illustrate the most important components of the network more simply, it is not described in more detail here that and how the air interface is set up to a base station of a mobile radio network, which is in turn connected to the communication network or a first MMS network environment DLA. The same also applies of course to the connection to the second mobile radio device described below). More precisely the first mobile radio device MFG1 is connected to a first MMS network environment DLA (MMSE: Multimedia Messaging Service Environment), which is in the area of responsibility of a first MMS provider. A software application, a so-called MMS user software application or MMS user agent MUAA, is provided on the mobile radio device MFG1 to implement the terminal-side element for the MMS. A so-called first MMS relay server MRSA is provided in the first MMS network environment DLA to provide the MMS functionality for the telecommunication devices or telecommunication terminals connected to the first MMS network environment.

The first MMS network environment DLA is connected in the example to a second MMS network environment DLB of a second MMS provider via an interface MM4 (see further description relating to figure 2), implemented for example via the SMTP (Simple Mail Transfer Protocol) protocol. A second MMS relay server MRSB is provided in the second MMS network environment to provide the MMS functionality for telecommunication devices or telecommunication terminals, such as the mobile radio device MFG2, connected to the second MMS network environment DLB. A software application is again provided on the mobile radio device MFG2, in this instance an MMS user application (MMS user agent) MUAB to implement the terminal-side element for the MMS. If multimedia messages are to be transmitted, in particular with useful data objects, from the mobile radio device MFG1 to the mobile radio device MFG2, the two MMS relay servers MRSA and MRSB can be combined in the MMS network environments DLA and DLB to form a switching component, as will be described later with reference to figure 3.

It is a characteristic feature of MMS that, for delivery of multimedia messages (MMs) to a receive device (mobile radio ~~device~~ device), it is possible to decide between so-called PUSH mode, in which an incoming message is transmitted immediately by an MMS relay server to the MMS user application of the receive device, and so-called PULL mode, in which the recipient or receive device is first informed about a multimedia message that has just arrived at the MMS relay server by means of an MMS notification or recipient notification message and can then itself decide whether or when it will download said multimedia message to its mobile radio device from the MMS relay server.

Possible defined interfaces for connecting further network elements or network components to an MMS relay server MRS, such as the MMS relay server MRSA or MRSB, are shown in figure 2. In addition to an interface MM1, via which an MMS user application MUAA and an MMS relay server are connected, any external servers, such as email servers EES, fax servers EFS, further message servers e.g. for UMS (Unified Message Services) ENS or other servers ESS, etc. can be connected to the MMS relay server MRS via interfaces MM3. External or “foreign” MMS providers are connected via an interface MM4, as already stated with reference to figure 1. An interface MM5 connects the MMS relay server MRS to the HLR (Home Location Register) of a mobile radio network operator, in which the individual customer data or user data of every mobile radio subscriber is stored (the HLR is generally located in the area of responsibility of the network operator, who does not necessarily have to be the same as the MMS provider). An interface MM6 allows the connection of one or more MMS user databases MUDB. ~~An interface~~Interface MM7 allows the connection of servers MVS operated by a VASP (Value Added Service Provider), which provide value added services to MMS users. ~~Finally there is a~~ further interface MM8 is provided for connecting a network unit or charging unit VE to the MMS relay server MRS, in which all the information of relevance to charging for the MMS is collected and evaluated. ~~An interface~~Interface MM2 provides a connection between relay and server in the MMS relay server MRS.

The exchange of data, in particular of useful data objects, between the MMS units or MMS data transmission units shown in figure 1 during transmission of a multimedia message MMA with multimedia message elements MME from the mobile radio device MFG1 and receipt by the mobile radio device MFG2 based on so-called abstract messages as defined according to the 3GPP is described in more detail below with reference to figure 3. An abstract message comprises at least one information element. When the MMS is used, a sender, in this instance the mobile radio device MFG1 or the MMS user application MUAA, can send a multimedia message MMA via the air interface MM1 to the MMS relay server MRSA of its MMS provider with the abstract message (also referred to below as a transmission message) "MM1_submit.REQ". The MMS relay server MRSA confirms correct receipt of the multimedia message from the MMS user application MUAA with the abstract message "MM1_submit.RES". The MMA is transmitted to the MMS relay server MRSB in the MMS environment DLB (see figure 1) of the recipient or destination mobile radio device with the abstract message pair "MM4_forward.REQ" (contains the actual multimedia message) and "MM4_forward.RES" (which sends a return message or confirmation back to the MMS relay server MRSA). The receive device MFG2 or its MMS user application MUAB is then informed of the multimedia message MMA available for downloading on the MMS relay server MRSB with the abstract message or recipient notification message "MM1_notification.REQ". This MMS recipient notification message contains the URI (Uniform Resource Identifier) of the storage location of the multimedia message on the MMS relay server MRSB as reference. The abstract message "MM1_notification.RES" primarily serves as confirmation of the correct receipt of the recipient notification message at the MMS user application MUAB and to inform the MMS provider of the nature of delivery required (PUSH or PULL mode). The recipient, namely the MMS user application MUAB, can use the abstract message or delivery request message "MM1_retrieve.REQ" to initiate the downloading of a multimedia message MMA available on the MMS relay server MRSB. The multimedia message MMA is delivered from the MMS relay server MRSB to the MMS user application MUAB

by means of the abstract message or delivery message “MM1_retrieve.RES”. The MMS relay server MRSB can be informed by the MMS user application MUAB of the outcome of the download of the multimedia message MMA with the abstract message “MM1_acknowledgement.REQ”. It should be noted that for a simple illustration of the transmission of a multimedia message from the mobile radio device MFG1 via the two MMS relay servers MRSA and MRSB to the mobile radio device MFG2, the two MMS relay servers MRSA and MRSB can also be seen as one switching component VK between the mobile radio devices. If the mobile radio device MFG2 was also in the effective area of the MMS environment of the first MMS provider, the switching component VK would only comprise the MMS relay server MRSA.

If a mobile radio network operator deploys a WAP implementation of MMS in ~~their~~ the PLMN (Public Land Mobile Network), the interface MM1 as described above ~~when examined more closely comprises~~ preferably comprises two sections connected together by a special network component, such as a ~~so-called~~ WAP (Wireless Application Protocol) gateway. The WAP gateway between an MMS relay server of an MMS provider and the core network of a mobile radio system or mobile radio network primarily has the task of adapting the data to be transmitted to the different protocol layers on both sides. To explain this more clearly, figure 4 shows a detailed configuration of the interface MM1 for the WAP implementation of MMS between a mobile telecommunication terminal, such as a mobile radio device, with an MMS user application MUA and an MMS relay server MRS. On the “A side” (in the direction of an external IP (internet protocol) network) the session layer protocol used is http (hypertext transfer protocol) and on the “B side” (in the direction of a mobile radio system or mobile radio network, PLMN) WSP (Wireless Session Protocol) is used.

~~It is now possible for~~ Accordingly, an MMS provider ~~to~~ may individually adapt a the multimedia message to be delivered or the useful data objects contained therein before sending an MMS recipient notification or recipient notification message. Such an adaptation can ~~for example~~ be based on the individual characteristics of the receive device, the individual user settings or any descriptive

information contained in a multimedia message or obtained from a multimedia message (so-called metadata, for example according to the MPEG-7 standard). Combinations of these three options are also possible. This is described in more detail below.

1. Adaptation of a multimedia message or the useful data objects contained therein according to the individual characteristics of the receive device: mobile radio devices, such as mobile telephones, are generally differentiated on the basis of their characteristics or capabilities. The characteristics of the display devices can sometimes vary significantly for example (e.g. in size and resolution), as can their capabilities in respect of displaying and/or processing certain file types and/or file formats. So that a mobile radio network operator or service provider can ~~get to know~~ the characteristics or capabilities of a WAP-enabled terminal, the WAP Forum has standardized the so-called UA Prof (User Agent Profile), with which the appropriate characteristic device profile can be assigned on the network side to every individual terminal or mobile radio device registered in the mobile radio network.

~~In the future~~ WAP UA Prof ~~will~~ may also be used with the MMS as follows: If a mobile radio customer or mobile radio user has a terminal or mobile radio device with a WAP-based MMS user application and is registered to use the MMS with an MMS provider, MMS-specific inputs will also represent a subset of the UA Prof or user profile (e.g. maximum size of incoming multimedia messages, etc.). The MMS relay server can access the user profile information via the interface MM6 shown in figure 2 (MMS relay server to MMS user database(s) MUDB). If an MMS provider has knowledge of the individual characteristics or capabilities of a mobile telecommunication terminal (e.g. mobile radio device) and an MMS user application (MMS user agent) installed thereon, the MMS relay server can specifically convert individual multimedia message elements or useful data objects to file types or formats suitable for the recipient's terminal before transmitting an MMS recipient notification (recipient notification message), so that the multimedia message can be displayed in an optimum fashion on the recipient's terminal.

2. Adaptation of a multimedia message according to individual user settings: In the MMS every user can apply settings on the network side, thereby configuring the MMS to their individual preferences. For example a user setting could be that all incoming multimedia messages containing multimedia message elements or useful data objects of a specific data type are automatically forwarded without an MMS recipient notification (recipient notification message) to an email address.

3. Adaptation of a multimedia message according to the metadata contained in a multimedia message: Descriptive information (so-called metadata) may also be contained in a multimedia message or be obtained from a multimedia message and this can be used to clarify the significance of individual multimedia message elements (useful data objects) and express dependencies between the individual multimedia message elements (useful data objects). For example a multimedia message element (useful data object) of the type “text” could be identified as the main component, a multimedia message element of the type “still” as the background image or a multimedia message element of the type “audio” as a (spoken) commentary relating to the still.

An incoming multimedia message can be adapted in the MMS relay server in the recipient-side MMS environment on the basis of the three data records described above (and combinations thereof) before transmission of the MMS recipient notification (recipient notification message).

So that the recipient has greater control of the multimedia message to be received and the useful data objects contained therein and receives information about whether and how a multimedia message or the elements or useful data objects contained therein has/have been adapted, the following is proposed according to an embodiment of the invention.

In the exemplary embodiment a number of alternative MMS recipient notifications (recipient notification messages) can be sent to the recipient for differently adapted variants of the same multimedia message. This gives the recipient a number of alternative options for downloading the same multimedia message. Variant here refers both to the original message and the useful data

objects contained in the original message as well as the adapted message and the adapted useful data objects.

To achieve this, a backward-compatible mapping mechanism ~~is proposed,~~ which allows assignment of the individual MMS recipient notifications (recipient notification messages) to a multimedia message in the MMS user application of the recipient.

It is ~~of course~~ also possible to pack the information about the different download options for the individual variants into a single, newly defined multipart MMS recipient notification but backward-compatibility would then not be possible. An old or conventional MMS user application (MMS user agent) could not start anything with the new and to it unknown structure of a multipart MMS recipient notification.

So that the alternative options for downloading an MM (in the different variants) are possible in a fashion that can easily be understood by the recipient, a possible configuration of the HMI (Human Machine Interface, for example in the form of a display) on the side of the receiving MMS user application (MMS user agent) is described below according to the disclosed embodiment.

To improve the control options when downloading a multimedia ~~message~~ message, a number of download options for the same multimedia message are to ~~be~~ preferably offered or transmitted to a recipient or a receiving device by creating and sending a number of different MMS recipient notifications (recipient notification messages) for variants of a multimedia message adapted differently on the network side (in particular by the MMS relay server of the MMS environment of the recipient's MMS provider) based on at least one of the following data records:

i) Information about the individual characteristics or capabilities of the mobile telecommunication terminal, such as a mobile radio device or mobile telephone, and the MMS user application (MMS user agent) installed thereon or connected thereto. The information about the individual characteristics or capabilities of a telecommunication terminal or a telecommunication device and the MMS user application (MMS user agent) in this respect could for example be

configured according to a WAP user profile or WAP UA Prof and could possibly originate from previous WSP sessions, i.e. earlier MMS download processes;

ii) Information about the individual preferences of the MMS user. The information about the individual user preferences in this respect could for example be a component of the MMS user database(s) MUDB (see also figure 2); and/or

iii) Descriptive information (so-called metadata), which clarifies the significance of individual multimedia message elements (useful data objects) and/or expresses relationships or dependencies between individual multimedia message elements. The descriptive information (metadata) in this respect could for example be configured according to MPEG-7 and could possibly be contained as an independent multimedia message element (useful data object) in the multimedia message or be obtained by the adapting MMS relay server from an incoming multimedia message.

The use of a backward-compatible mapping mechanism for MMS recipient notifications (recipient notification messages) also serves to improve control options:

a) Associated MMS recipient notifications are advantageously identified by an additional newly defined header field in the adapting MMS relay server before delivery to the recipient's MMS user application;

b) A sequence number can also be advantageously used (again in a newly defined header field) in order to be able to establish in the recipient's MMS user application whether all the associated MMS recipient notifications have arrived. It should also be clear from the sequence information in the respective different recipient notification messages which of the MMS recipient notifications relate to the unmodified original version of the at least one useful data object. For example the value "0" for the sequence number could indicate the original version, while values > 0 indicate adapted/modified versions of useful data objects or transmission messages (i.e. multimedia messages MM);

c) ~~Finally-Also,~~ the individual MMS recipient notifications can be assigned in the recipient's MMS user application (MMS user agent) based on identification numbers and sequence numbers.

As an alternative to a) and b)b), the ID for associated MMS recipient notifications and/or the sequence number and/or a maximum number indicating the total number of variants provided or the total number of MMS recipient notifications generated or sent could also be specially coded and integrated into an already known header field (for example as an additional parameter).

The control options and the information to a recipient of a multimedia message can also be further improved by displaying the information from the individual MMS recipient notifications relating to alternative download options, i.e. for different variants of a multimedia message or its useful data objects, in a user-friendly fashion by means of a particularly advantageous configuration of the HMI in the recipient MMS user application (MMS user agent).

~~Examples~~ Further are described below to clarify the aspects mentioned above relating to improving the control options when downloading multimedia messages available on an MMS relay server:

A. Provision of alternative download options

~~We will first look further at the aspect of providing alternative~~ Alternative download options may be provided for the same multimedia message by creating and sending a plurality of different MMS recipient notifications (recipient notification messages) for variants of a multimedia message adapted or processed differently on the network side.

The examples below are all based on the assumption that an exemplary multimedia message, comprising three multimedia message elements or useful data objects (MME), namely a 20 kB text, an image with 8 bit color depth and a 30 kB voice note is to be sent from a sender (i.e. from a first telecommunication device, such as a mobile radio device) to a recipient (i.e. a second telecommunication device, such as a second mobile radio device), as already described with reference to figure 3. However in contrast to the description above with reference to figure 3, at least one useful data object is now adapted or modified as a function of the information described under points i) to iii) in the MMS environment of the recipient's MMS provider, in particular in their MMS relay server (with reference to figure 3 this would be the MMS relay server MRSB, if the multimedia message

MMA is sent by the mobile radio device MFG1), before transmission of the at least one MMS recipient notification (recipient notification message).

Example 1: Creation of a plurality of MMS recipient notifications for one multimedia message (MMA) based on the individual characteristics or capabilities of the mobile telecommunication terminal and the MMS user application (MMS user agent)

The MMS relay server (~~according to~~ using to the above assumption the MMS relay server MRSB, see figure 3) is to deliver the exemplary multimedia message (MMA) to the MMS user application (MMS user agent) MUAB of the recipient, the mobile radio device MFG2. In a data record stored on the network side (see point i above) containing the individual characteristics and capabilities of the mobile radio device MFG2 and the MMS user application MUAB it is ~~for example~~ noted that the receive device MFG2 can only display black and white images in the example. The user (of the mobile radio device MFG2) may however still wish to download a color image from the MMS relay server MRSB, wishing to print out the multimedia message element (useful data object) in color later.

The MMS relay server (MRSB) of the exemplary embodiment now creates a further multimedia message variant with a different color depth for the image or image data object from the original, according to the rules of the data record with the individual characteristics and capabilities of the mobile telecommunication terminal, in addition to the received multimedia message (MMA). This is shown in table 1 below, in which the MMS relay server has created an adapted multimedia message variant 1B from the original multimedia message variant 1A, having a black and white image with a different depth of color instead of the color image. The multimedia messages elements of the types “text” and “audio” remain the same:

	MM variant 1A	MM variant 1B
Text	Original	Original
Text size	20 kB	20 kB
Image	Original	Modified
Resolution	100 x 80 pixels	100 x 80 pixels

Depth of color	8 bit	2 bit
Image size	8 kB	2 kB
Audio	Original	Original
Audio size	30 kB	30 kB

Table 1

In a next step the MMS relay server MRSB creates a specific MMS recipient notification for the original multimedia message variant 1A and the newly generated multimedia message variant 1B respectively. Both MMS recipient notifications refer to the same content in principle, which is now present in two differently adapted variants. Each multimedia message variant is referred to by its own URI. The respective MMS recipient notifications “MM1_notification.REQ(s)” are then sent, as shown in figure 3, from the MMS relay server MRSB to the receive terminal MFG2 (adding “(s)” to “MM1_notification.REQ” in figure 3 indicates that according to the embodiment of the invention a plurality of MMS recipient notifications or recipient notification messages are now sent to the recipient based on one multimedia message (MMA)).

Example 2: Creation of a plurality of MMS recipient notifications for one multimedia message (MMA) based on the individual preferences of the MMS user

Again with reference to figure 3 the MMS relay server MRSB is to deliver the exemplary multimedia message MMA to the MMS user application (MMS user agent) MUAB of the recipient or mobile radio device MFG2. ~~It is for example~~ In it the example is marked in a data record stored on the network side and containing the individual preferences of the MMS user (according to point ii)) that all the images contained in a multimedia message should be scaled down in two user-defined stages before delivery of the multimedia message (a depth of color reduction would of course also be possible). The recipient ~~has possibly applied~~ may apply these settings to minimize the data volume as far as possible both when delivering the multimedia message via the interface MM1 and when storing the multimedia message in their mobile telecommunication device. This could reduce download costs (depending on the MMS provider’s charging model) and also

means that a larger number of multimedia messages could be stored in the receive terminal. The MMS relay server MRSB now creates two further variants 2B and 2C according to the rules of the data record with the individual preferences in addition to the received original multimedia message MMA (multimedia message variant 2A) (more precisely variants of the image or image object are generated, the text and audio objects remaining in the original form). These further variants differ in image format, as shown in table 2 below:

	MM variant 2A	MM variant 2B	MM variant 2C
Text	Original	Original	Original
Text size	20 kB	20 kB	20 kB
Image	Original	Modified	Modified
Resolution	100 x 80 pixels	75 x 60 pixels	50 x 30 pixels
Image size	8 kB	4.5 kB	1.5 kB
Audio	Original	Original	Original
Audio size	30 kB	30 kB	30 kB

Table 2

In a next step the MMS relay server MRSB creates a specific MMS recipient notification for the original multimedia message variant 2A and the two newly generated multimedia message variants 2B and 2C respectively. All three refer to the same content in principle, which is now present in three different or adapted variants. Each multimedia message variant is referred to by its own URI. The respective MMS recipient notifications “MM1_notification.REQ(s)” are then sent, as shown in figure 3, from the MMS relay server MRSB to the receive terminal MFG2 (adding “(s)” to “MM1_notification.REQ” in figure 3 again indicates that according to the embodiment of the invention a plurality of MMS recipient notifications or recipient notification messages are now sent to the recipient based on one multimedia message (MMA)).

Example 3: Creation of a plurality of MMS recipient notifications for one multimedia message (MMA) based on metadata (significance or dependencies between individual multimedia message elements or useful data objects)

Again with reference to figure 3 the MMS relay server is to deliver the exemplary multimedia message MMA to the MMS user application (MMS user agent) of the recipient or the receive device MFG2. The descriptive information (see point iii)) clarifies the relationship of the individual multimedia message elements (useful data objects) in the example as follows: The text or text object is the main message and is independent of the other two multimedia elements. The multimedia message element of the type “audio” contains a spoken commentary relating to the multimedia message element of the type “image” or “still” and is meaningless without the image. (For example: “If you look closely you can see our holiday home in the background”). The receive terminal MFG2 may not be able to display images. (Ideally this information would be a component of the individual characteristics and capabilities of the mobile radio device MFG2 and the MMS user application (MMS user agent) MUAB according to example 1). The MMS relay server MRSB can now identify from the metadata that the audio object or audio file is pointless to the recipient without the still and can generate one or more correspondingly adapted multimedia message variants and invite the user to download according to table 3 below:

	MM variant 3A	MM variant 3B	MM variant 3C
Text	Original	Original	Original
Text size	20 kB	20 kB	20 kB
Image	Original	Deleted	Deleted
Resolution	100 x 80 pixels	n/a	n/a
Image size	8 kB	n/a	n/a
Audio	Original	Original	Deleted
Audio size	30 kB	30 kB	n/a

Table 3

In a next step the MMS relay server MRSB creates a specific MMS recipient notification or recipient notification message for the original multimedia message

variant 3A and the two newly generated multimedia message variants 3B and 3C respectively. All refer to the same content in principle, which is now present in three differently adapted variants. Each multimedia message variant is referred to by its own URI. The respective MMS recipient notifications “MM1_notification.REQ(s)” are then sent, as shown in figure 3, from the MMS relay server MRSB to the receive terminal MFG2 (adding “(s)” to “MM1_notification.REQ” in figure 3 again indicates that according to the embodiment of the invention a plurality of MMS recipient notifications or recipient notification messages are now sent to the recipient based on one multimedia message (MMA)).

B. Use of a backward-compatible mapping mechanism for MMS recipient notifications

Again with reference to figure 3 and in particular further to the examples mentioned above under point A, which identify different MMS recipient notifications “MM1_notification.REQ(s)” as associated in the MMS user application (MMS user agent) of the recipient, the MMS relay server MRSB assigns a unique identification number for every originally received multimedia message and extends this together with a maximum number, i.e. a total number of generated or sent MMS recipient notifications, and an optional sequence number for the MMS recipient notifications in every individual MMS recipient notification. The individual MMS recipient notifications or recipient notification messages “MM1_notification.REQ(s)” are then sent in ~~the a~~ conventional manner to the MMS user application (MMS user agent) of the recipient or receive device. All the associated MMS recipient notifications “MM1_notification.REQ(s)” can now be displayed there in a ~~standard~~ manner that is ~~extremely~~ convenient for the user on the basis of the identification number added by the MMS server relay. By counting the received associated MMS recipient notifications and then comparing the resulting value with the maximum number, the MMS user application (MMS user agent) of the receive device (in this instance the mobile radio device MFG2) is able to establish in a simple fashion whether all the associated MMS recipient notifications “MM1_notification.REQ(s)” have arrived.

By way of an example of implementation of the MMS using WAP below, the individual MMS recipient notifications are shown in text coding according to example 2 under point A, in which the image size of a multimedia message element (useful data object) of the type “still” or “image” is reduced in two stages. It should be pointed out that in WAP the “M-Notification.ind” PDU (Protocol Data Unit) corresponds to the above-mentioned abstract message “MM1_notification.REQ” according to 3GPP. According to ~~one embodiment of the invention~~this embodiment, new headers are inserted into the MMS recipient notifications in boxes for the identification number and the sequence number. More precisely the notification 1 shows an MMS recipient notification (WAP-PDU-“M-Notification.ind”) for the multimedia message variant 2A (large image), the notification 2 shows an MMS recipient notification (WAP-PDU-“M-Notification.ind”) for the multimedia message variant 2B (medium size image) and the notification 3 shows an MMS recipient notification (WAP-PDU-“M-Notification.ind”) for the multimedia message variant 2C (small image).

Notification 1:

X-Mms-Message-Type: m-notification-ind

X-Mms-Transaction-ID: abc10

X-Mms-Version: 1.0

From: andreas.st.schmidt@siemens.com

Subject: A multimedia message

X-Mms-Message-Class: Personal

X.Mms-Message-Size: 58000

X-Mms-Expiry: 36000

X-Mms-Variant-Id: example-xyz

X-Mms-Max-Notifications: 3

X-Mms-Sequence-Number: 1

X-Mms-Content-Location: <http://operator.de/inbox/mm-id-2A>

Notification 2:

X-Mms-Message-Type: m-notification-ind
X-Mms-Transaction-ID: abc12
X-Mms-Version: 1.0
From: andreas.st.schmidt@siemens.com
Subject: A multimedia message
X-Mms-Message-Class: Personal
X-Mms-Message-Size: 54500
X-Mms-Expiry: 36000

X-Mms-Variant-Id: example-xyz X-Mms-Max-Notifications: 3 X-Mms-Sequence-Number: 2

X-Mms-Content-Location: <http://operator.de/inbox/mm-id-2B>

Notification 3:

X-Mms-Message-Type: m-notification-ind
X-Mms-Transaction-ID: abc16
X-Mms-Version: 1.0
From: andreas.st.schmidt@siemens.com
Subject: A multimedia message
X-Mms-Message-Class: Personal
X-Mms-Message-Size: 51500
X-Mms-Expiry: 36000

X-Mms-Variant-Id: example-xyz X-Mms-Max-Notifications: 3 X-Mms-Sequence-Number: 3

X-Mms-Content-Location: <http://operator.de/inbox/mm-id-2C>

It should be pointed out that the principle described can also be applied not only to simple or simplified MMS recipient notifications with the basic information but also to detailed MMS recipient notifications, which contain more detailed descriptions of the individual multimedia message elements. The benefit of this

invention for such detailed MMS recipient notifications can thereby be even greater.

It is also possible according to an advantageous embodiment for the unique identification number of the multimedia message, the maximum number and the sequence number to be contained in code in the URI (preferably in the last part of the path details).

C. User-friendly display of information from the individual MMS recipient notifications relating to alternative download options by means of a particularly advantageous embodiment of the HMI in the MMS user application (MMS user agent)

As mentioned above, the method described above provides a particularly advantageous embodiment of the menu guide in the MMS user application of the receive device, as the MMS user application:

- identifies associated MMS recipient notifications for different variants of a multimedia message based on the unique identification ~~number and~~number; and
- knows from the maximum number how many multimedia message variants the MMS relay server has provided for a specific multimedia message (identified by the same identification number); and
- identifies from the sequence number which MMS recipient notification belongs to the multimedia message originally received by the MMS server (without adaptation).

Figure 5 shows a first exemplary user interface BOF1 displayed on a display unit of the receive device, on which interface the respective MMS recipient notifications or recipient notification messages from example 2 described above under point A are processed and the information contained in them is clearly displayed. It is now shown that there is a multimedia message with three alternative variants or download options in the MMS inbox dated 02.11.2002. The sender, subject of the message, category, size of the modified multimedia message element (in this instance the image) and validity of the multimedia message are also shown.

Finally the user of the receive device is prompted to select a variant of the multimedia message element or multimedia message. The required download option can be selected by pressing the corresponding key on a keypad of the receive device (the mobile radio device MFG2 in the example in figure 3).

If detailed MMS recipient notifications are used, other information that may be contained in an MMS recipient notification is advantageously also displayed to the user, as shown in figure 6, on a second user interface BOF2 of the receive device (for example the mobile radio device MFG2 in figure 3). As well as the information already shown in figure 5, it is also displayed that there is a multimedia message with three alternative variants or download options in the MMS inbox dated 03.11.2002, with additional details of which variant is the original variant and which multimedia message elements are provided in the multimedia message variants available on the MMS relay server. One or more required variants or download options can be selected by pressing the corresponding key on a keypad of the receive device or by selecting a corresponding selection surface AWF by means of a mouse pointer MZ and correspondingly confirming the selection.

It should be understood that the various changes and modifications to the presently preferred embodiments described herein will be apparent to those skilled in the art. Such changes and modifications can be made without departing from the spirit and scope of the present disclosure and without diminishing its intended advantages. It is therefore intended that such changes and modifications be covered by the appended claims.

ABSTRACT

The ~~invention~~ present disclosure relates to a method for transmitting messages, ~~comprising the following steps:~~ a transmission message (~~MMA~~, ~~MM1_submit.REQ~~) containing one or more useful data objects (~~MME~~) is first transmitted to a switching component (~~VK~~) in order to be routed to a second telecommunications device (~~MFG2~~), ~~said wherein the transmission being is made~~ by a transmitting telecommunications device, (~~MFG1~~); a plurality of variants of the one or more useful data objects is created in the switching component in accordance with a set of parameters, the second telecommunications device is then informed (~~MM1_notification.REQ~~) of the provision of the plurality of variants of ~~said one or more~~ the data objects for transmission to the second telecommunications device; ~~preferably,~~ Also, a delivery request message (~~MM1_retrieve.REQ~~) relating to a specific variant of the ~~one or more~~ useful data objects is subsequently sent from the second telecommunications device to the switching component; ~~the~~ The switching component then transmits a delivery message containing the requested variant of the ~~one or more~~ useful data objects to the second telecommunications device.

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of claims:

Claims 1-28 (canceled).

Claim 29 (new): A method for transmitting messages in a communication network, comprising:

transmitting a transmission message containing one or more useful data objects to a switching component for forwarding to a first telecommunication device;

creating a plurality of variants of the one or more useful data objects in the switching component as a function of one or more parameters; and

informing the first telecommunication device of the availability of a plurality of variants of the one or more useful data objects for transmission to the first telecommunication device.

Claim 30 (new): The method according to claim 28, further comprising:

transmitting a delivery request message requesting a specific variant of the one or more useful data objects from the first telecommunication device to the switching component;

transmitting a delivery message containing the requested variant of the one or more useful data objects from the switching component to the first telecommunication device.

Claim 31 (new): The method according to claim 29, wherein the step of informing the telecommunication device comprises:

generating respective recipient notification messages assigned to a specific variant of the one or more useful data objects; and

transmitting the respective recipient notification messages from the switching component to the first telecommunication device.

Claim 32 (new): The method according to claim 28, wherein the parameters includes parameters with information about the individual characteristics of the telecommunication device and in particular about applications provided on the telecommunication device.

Claim 33 (new): The method according to claim 28, wherein the parameters includes parameters with information about the individual preferences of the recipient.

Claim 34 (new): The method according to claim 28, wherein the parameters include parameters with descriptive information, which includes the significance of useful data objects contained in the transmission message and/or the relationships between contained useful data objects.

Claim 35 (new): The method according to claim 28, wherein the transmission message is transmitted from a second telecommunication device to the switching component.

Claim 36 (new): The method according to claim 30, wherein the transmission message, delivery request message, delivery message, and recipient notification messages are transmitted in the context of the multimedia messaging service between the first telecommunication device and the switching component and/or the second telecommunication device and the switching component.

Claim 37 (new): The method according to claim 35, wherein the messages to and from the first telecommunication device and/or the second telecommunication device are sent via an air interface.

Claim 38 (new): The method according to claim 36, wherein the first and/or second telecommunication device comprises a radio module.

Claim 39 (new): The method according to claim 36, wherein messages to and from the first and/or second telecommunication device are transmitted by means of the WAP protocol WSP and/or the hypertext transfer protocol.

Claim 40 (new): The method according to claim 38, wherein the first telecommunication device is part of a first telecommunication network.

Claim 41 (new): The method according to claim 39, wherein the first telecommunication network is configured as a mobile radio network, operating according to the GSM, GPRS, EDGE, UMTS or CDMA standard.

Claim 42 (new): The method to claim 39, wherein the switching component is configured as part of a second telecommunication network connected to the first telecommunication network, which operates under the hypertext transfer protocol.

Claim 43 (new): The method according to claim 41, wherein the first and second telecommunication networks are connected together by a WAP gateway.

Claim 44 (new): The method according to claim 37, wherein the recipient notification message is transmitted to the telecommunication device by WAP push.

Claim 45 (new): The method according to claim 43, wherein the switching component is configured as an MMS relay server.

Claim 46 (new): The method according to claim 44, wherein the recipient notification messages, which are assigned to variants of useful data objects of a specific transmission message, comprise specific standard identification information.

Claim 47 (new): The method according to claim 45, wherein the recipient notification messages, which are assigned to variants of useful data objects of a specific transmission message, further comprise total information, indicating the total number of recipient notification messages generated by the switching component for the variants of the one or more useful data objects of a transmission message.

Claim 48 (new): The method according to claim 46, wherein different recipient notification messages have sequence information, which contains the sequence of the variants of the one or more useful data objects generated by the switching component.

Claim 49 (new): The method according to claim 47, wherein the different recipient notification messages have differentiation information, which indicates whether a variant of a useful data object assigned to a respective recipient notification message is the original variant contained in the transmission message or a modified variant.

Claim 50 (new): The method according to claim 48, wherein the sequence information in the different recipient notification messages indicates which of the recipient notification messages relates to the unmodified original version of the at least one useful data object or the transmission message.

Claim 51 (new): The method according to claim 47, wherein the identification information and/or the total information and/or the sequence information is provided under a respectively independent header field in a recipient notification message.

Claim 52 (new): The method according to claim 47, wherein the identification information and/or the total information and/or the sequence information together is coded in a recipient notification message.

Claim 53 (new): The method according to claim 47, wherein the identification information and/or the total information and/or the sequence information is processed by the first telecommunication device on receipt of a respective recipient notification message.

Claim 54 (new): The method according to claim 52, wherein the variants for transmission by the switching component are displayed on a user interface so that a user can select one or more variants and request transmission by the switching component.

Claim 55 (new): The method according to claim 53, wherein the useful data objects contain text information, audio information, video information, executable programs, software modules or a combination of such information.

REMARKS

The present amendment makes editorial changes and corrects typographical errors in the specification, which includes the Abstract, in order to conform the specification to the requirements of United States Patent Practice. No new matter is added thereby. Attached hereto is a Substitute Specification including a marked-up version of the changes made thereto via by the present amendment.


In addition, the present amendment cancels original claims 1-1-28 in favor of new claims 29-55. Claims 29-55 have been presented solely because the revisions by red-lining and underlining which would have been necessary in claims 1-15 in order to present those claims in accordance with preferred United States Patent Practice would have been too extensive, and thus would have been too burdensome. The present amendment is intended for clarification purposes only and not for substantial reasons related to patentability pursuant to 35 U.S.C. §§101, 102, 103 or 112. Indeed, the cancellation of claims 1-1-28 does not constitute an intent on the part of the Applicants to surrender any of the subject matter of claims 1-1-28.

Early consideration on the merits is respectfully requested.

Respectfully submitted,

BELL BOYD & LLOYD LLC

BY


Peter Zura

Reg. No. 48,196

Customer No. 29177

Phone: (312) 807-4208

Dated: December 6, 2005